# **D16**

### Bronze Globe Valve - Series A

PN32\*

#### **Features & Benefits**

- Crane Bronze globe valves are highly efficient for throttling because seat and disc designs provide flow characteristics with proportionate relationships between valve lift and flow rate
- \*Please note Sizes 21/2" and 3" are rated at PN25

#### **Materials**


PART	MATERIAL	SIZES
Body	Bronze BS EN 1982 CC491K	All
Bonnet	Bronze BS EN 1982 CC491K	All
Body Seat Ring	13% Cr.Steel BS970 Pt.1 410S21 or 431S29	All
Disc Stem Ring	Brass BS EN 12163 CW721R	All
Disc	13% Cr.Steel BS970 Pt.1 410S21 or 431S29	1/2 - 2
Disc	Nickel Alloy	$^{1}/_{4}$ , $^{3}/_{8}$ , $2^{1}/_{2}$ & 3
Stem	Manganese Bronze BS EN 12163 CW721R	All
Gland	Brass BS EN 12164 CW614N	All
Packing	Asbestos Free	All
Packing Nut	Brass BS EN 12164 CW614N	<sup>1</sup> /4 - 2 <sup>1</sup> /2
Packing Nut	Bronze BS EN 1982 CC491K	3" only
Handwheel	Aluminium	1/4 - 21/2
Handwheel	Malleable Iron BS EN 1562 GJMB-300-6	3" only
Handwheel Nut	Brass BS EN 12164 CW614N	All
ID Plate	Aluminium	All
Gasket	Asbestos Free	21/2 - 3

### **Dimensions & Weights**

SIZE (inch)	WEIGHT (kg)	A (mm)	B (mm)	C (mm)	1
1/4	0.33	52	100	52	
3/8	0.31	52	100	52	
1/2	0.8	62	101	52	
3 <sub>/4</sub>	1.24	74	115	52	
1	1.5	90	125	70	
1 <sup>1</sup> /4	1.7	100	150	70	
1 <sup>1</sup> /2	2.16	115	159	92	
2	3.67	136	191	103	
21/2	6	166	220	121	
3	10.9	190	255	178	



## **Dimensional Drawing**



### **Pressure/Temperature Ratings**

TEMPERATURE (°C)	-10 to 100	260	
PRESSURE (BAR)	32	14	

Intermediate pressure ratings shall be determined by interpolation.

PRESSURE RATING: PN32
TEMPERATURE OPERATING RANGE: -10 to 260°C

**UK END CONNECTION:** Taper threaded to BS EN 10226-2 (ISO 7-1) formerly BS 21

**US END CONNECTION:** ANSI B1.20.1

**OPERATOR:** Handwheel

SPECIFICATION: Valves are manufactured in accordance with BS 5154: 1991 Series A, PN32 for sizes <sup>1</sup>/<sub>4</sub>" to 2" and PN25 for sizes 2<sup>1</sup>/<sub>2</sub>" and 3".

Design incorporates a nickel alloy plug type disc retained on the stem by a threaded ring; body seat is a screwed-in stainless steel ring.

This valve is not suitable for use on group 1 gases or unstable fluids, as defined by the Pressure Equipment Directive 97/23/EC.\*

\* See page 230 for more information

Valid as of 010412

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.